MP220PII Classroom Amplifier



Features

- 100V power signal input, with priority function.
- 2 microphone inputs, and 2 aux inputs
- With individual volume control for each channel
- Override function, and can turn on the amplifier automatically when in emergency
- Perfect self-protection

Description

This Classroom broadcasting amplifier has 100V power signal input and is equipped with priority function. It has 2 microphone inputs, and 2 aux inputs. It can be hanging on the wall, and the turnover cover can be locked which is suitable for the classroom. Able to have microphone built-in.

Specification

Rated output	**20W（4Ωload）**
Output mode	4-16ΩRated output
Input sensitivity	MIC 1，2: 600Ω，≥5mV (-50dBV), unbalanced
	AUX1，2: 10 kΩ, ≥350mV (-10dBV),unbalanced
	LINE IN：≥30V，Rated power
Frequence response	LINE IN, MIC: 150Hz-15kHz AUX: 20Hz-20kHz
The ratio of signal to noise	Mic 1，2： ≤5mV
	AUX1，2： ≤1mV
	TREBLE: ±10dB at 10kHz
Capability of use	AC FUSE（2A）×1
Power requirements	AC 220-240V/50-60Hz
Power consumption	60W
Dimensions	250×220×80mm^3
Gross weight/net weight	4.5kg /3.2kg

Connection

